



AWMF-0240/AWMF-0241 Developer Kit User Guide

	AWMF-0240/AWMF-0241 Developer Kit User Guide	Document	AWMF-0240-AWMF-0241-DK-UG
		Issue Date	5/5/25
		Revision	1.0
		Page	1 of 11

Revision	Date	By	Description of Change
1.0	5/5/25	AMS	Initial version

1	CONTENTS	
2	IMPORTANT READ THIS SECTION FIRST	3
2.1	Power Up Instructions.....	3
2.2	Supported Devices.....	3
3	SOFTWARE INSTALLATION	4
3.1	FTDI USB-SPI Installation	4
3.2	Hardware Validation.....	6
3.3	AWMF0240 Control Software Installation	7
4	AWMF0240 SOFTWARE OPERATION.....	9
5	POWER UP PROCEDURE.....	10
5.1	Bias Configuration.....	10
5.2	Controller and Power Supply Connections	10
5.3	Additional Recommendations	11

	AWMF-0240/AWMF-0241 Developer Kit User Guide	Document	AWMF-0240-AWMF-0241-DK-UG
		Issue Date	5/5/25
		Revision	1.0
		Page	3 of 11

2 IMPORTANT READ THIS SECTION FIRST

2.1 Power Up Instructions

Prior to powering up the evaluation board it is critical that you review and carefully follow the procedure outlined in:

5 Power Up Procedure

Failure to follow this procedure can result in damage to the device

2.2 Supported Devices

The control software supports the AWMF0240 and AWMF0241. Features not supported by a specific device are managed by selecting the appropriate device type from the DevType drop down menu. For correct operation, it is important to select the recommended state file specific to that device.

3 SOFTWARE INSTALLATION

In order to control the evaluation board, two software installation steps are required. The first step is to install the necessary support software for the FTDI USB-SPI controller as described in 3.1. The second step is to install the Qorvo software specific to the evaluation board to provide the control user interface, as described in 3.3.

3.1 FTDI USB-SPI Installation

This section describes the software installation process for the FTDI USB-SPI controller. The software should be downloaded via the link provided in the AWMF0240-PK070 Quick Start Guide. The user should follow the installation steps detailed in Figure 1 to Figure 7. Note the USB-SPI controller should be connected to an available USB port upon successful installation of the driver software.




Figure 1: Copy CDM2123620_Setup.zip to a temporary folder. Double click to extract the files




Figure 2: Right-click CDM2123620_Setup and Run As Administrator

	AWMF-0240/AWMF-0241 Developer Kit User Guide	Document	AWMF-0240-AWMF-0241-DK-UG
		Issue Date	5/5/25
		Revision	1.0
		Page	5 of 11




Figure 3: Select Yes to continue installation

Device Driver Installation Wizard




Figure 5: Select Next

Device Driver Installation Wizard




Figure 7: Select Finish




Figure 4: Select Extract

Device Driver Installation Wizard




Figure 6: Accept agreement and select Next

	AWMF-0240/AWMF-0241 Developer Kit User Guide	Document	AWMF-0240-AWMF-0241-DK-UG
		Issue Date	5/5/25
		Revision	1.0
		Page	6 of 11

3.2 Hardware Validation

Once the FTDI software installation has successfully completed, the PCB-10077 USB-SPI controller board should be plugged into the PC using an available USB port. Successful installation and configuration can be confirmed if the red LED labelled DS1 is lit and that the USB Serial Converter A and USB Serial Converter B appear in the Device Manager as illustrated in Figure 8 and Figure 9, respectively.




Figure 8: USB-SPI Controller Board




Figure 9: Confirm Devices Are Present in Device Manager

If the driver does not install successfully, please refer to AN396 FTDI Drivers Installation Guide for Windows 10/11 from FTDI Chip (<https://ftdichip.com/>).

	AWMF-0240/AWMF-0241 Developer Kit User Guide	Document	AWMF-0240-AWMF-0241-DK-UG
		Issue Date	5/5/25
		Revision	1.0
		Page	7 of 11

3.3 AWMF0240 Control Software Installation

This section describes the steps necessary to install the Qorvo Developer Kit control software. The software should be downloaded via the link provided in the AWMF0240-PK070 Quick Start Guide. Follow the steps detailed in Figure 10 to Figure 16 to install the control software.




Figure 10: Download the Installer to a Temporary Folder and Run as Administrator




Figure 11: Select Yes and Continue




Figure 12: Select Next and Continue




Figure 13: Accept License Agreement and Continue




Figure 14: Select Folder for Software Installation




Figure 15: Create Shortcuts if Required




Figure 16: Complete Installation

	AWMF-0240/AWMF-0241 Developer Kit User Guide	Document	AWMF-0240-AWMF-0241-DK-UG
		Issue Date	5/5/25
		Revision	1.0
		Page	9 of 11

4 AWMF0240 SOFTWARE OPERATION

The control software can be operated in ‘simulation’ or ‘live’ modes and defaults to starting in ‘simulation’ mode. The ‘simulation mode’ does not require any hardware to be attached to the PC and is intended to help familiarize the user with the various controls and register write/read operations. Note that simulation mode does not emulate the behavior of the device (e.g. reading back from the temperature sensor or power detectors in simulation mode will return zeros). For correct operation in live mode, the SPI controller board should be connected to the PC and the EVB and the device should be powered up prior to making connection in the user interface. **The hardware connections and power up sequence detailed in Section 5 should be followed prior to starting the control software in live mode.**

	AWMF-0240/AWMF-0241 Developer Kit User Guide	Document	AWMF-0240-AWMF-0241-DK-UG
		Issue Date	5/5/25
		Revision	1.0
		Page	10 of 11

5 POWER UP PROCEDURE

Note that it is critical that the steps in the following section are carefully followed to avoid damage to the device.

5.1 Bias Configuration

It is recommended that a power supply capable of 4W operation is used for V_{DDA} , whilst 2W operation is used for $V_{DD_DIG_1P2}$. If a 4W supply is not available, then it is recommended to connect the Yellow and Green wires to the associated supply along with their respective ground lines. Power supply connections are provided in Table 1

Table 1: Power Supply Connectors with AWC9240 Cable

Pin	EVB Power Header Pin/Function	Cable Color	PSU Connection
1	V_{DDA}	Yellow	V_{DD} FORCE HI
2	Ground	Black	V_{DD} FORCE LO
3	V_{DDA}	Green	V_{DD} SENSE HI
4	Ground	Black	V_{DD} SENSE LO
5	n/c	-	-
6	Ground	-	-
7	$V_{DD_DIG_1P2}$	Purple	$V_{DD_DIG_1P2}$ HI
8	Ground	Black	$V_{DD_DIG_1P2}$ LO

5.2 Controller and Power Supply Connections

The cables should be connected as detailed in Table 2 and illustrated in Figure 17 and Figure 18.

Table 2: Connections Between DC/SPI Interposer Board and EVB

	TPCB1077V1A Controller Board	TAWMF0240EVBP1 Device Eval Board
SPI IO cable (FFTP-12-D-03.85-01-N)	P3	X2
Power cable (AWC9240)	-	P2

	AWMF-0240/AWMF-0241 Developer Kit User Guide	Document	AWMF-0240-AWMF-0241-DK-UG
		Issue Date	5/5/25
		Revision	1.0
		Page	11 of 11




Figure 17: Bottom side view: IO cable connected to X2



Figure 18: Top side view: Power cable connected to P2

5.3 Additional Recommendations

Any unused RF port should be terminated with a high quality 2.92 mm termination.